

# *Delta* 210HGN



## **Low-Pro Flatbed Trailer with Hydraulic Dovetail**



DELTA TRAILERS • 1-800-556-2283 • [www.deltatrailers.com](http://www.deltatrailers.com)



# 210HGN

## LOW-PRO 10K DUALY GOOSENECK WITH 9' HYDRAULIC DOVETAIL

### S P E C I F I C A T I O N S

<b>G.V.W.R</b>	23,400#
<b>COUPLER</b>	2 5/16" E-Z Adjustable Coupler
<b>AXLES</b>	Tandem 10,000# Dual Wheel (Oil-Bath)
<b>SUSPENSION</b>	Multi-leaf Slipper Spring with Equalizer
<b>TIRE</b>	ST235/80R16 (10 ply)
<b>WHEEL</b>	16 x 6 Dual 8-bolt
<b>FRAME</b>	12" I-Beam (Low-Pro Pierced Beam)
<b>NECK</b>	12" I-Beam
<b>CROSSMEMBERS</b>	3" Channel on 16" centers - Pierced thru Main Frame
<b>SAFETY CHAINS</b>	3/8" Heavy Duty with Safety Latch Hooks
<b>JACK</b>	12,000# Spring Loaded Drop Leg Jack
<b>SIDE RAILS</b>	5" Angle Iron with Rub Rails
<b>STAKE POCKETS</b>	Formed Stake Pockets on 24" centers
<b>FLOOR</b>	2" Pressure Treated Pine
<b>LIGHTS</b>	All LED Stop, Tail, Turn and Clearance

<b>ELECTRIC PLUG</b>	7-Way RV Style
<b>PREP</b>	3-Step Acid Washed with Phosphorus Solution
<b>PRIMER</b>	Rust Resistant Epoxy Primer
<b>PAINT</b>	High Solid Urethane
<b>PINSTRIPES</b>	Painted Pinstripes
<b>OVERALL WIDTH</b>	102" Wide (approx)
<b>DECK HEIGHT</b>	Approx. 33" Standard (Low-Pro Pierced Beam)
<b>BRAKES</b>	Electric Brakes on All Axles
<b>DOVE TAIL</b>	9' Self-Contained Hydraulic Dove Tail
<b>STEPS</b>	Access Step on Both Sides
<b>STORAGE</b>	Chain Basket Between Uprights
<b>WIRING</b>	Front Mount in Conduit
<b>REFLECTIVE TAPE</b>	Required D.O.T. Reflective Taping
<b>SAFETY</b>	Emergency Breakaway Switch & Battery Backup
	All specifications subject to change without notice.

### O P T I O N S

- Electric over Hydraulic Brakes
- Torque Tube (helps minimize trailer twisting)
- Disc Brakes (Includes 10K HD)-Must add Elec/Hydraulic
- Pipe Spools (between Stake Pockets)
- Dexter HD Adjustable Suspension (similar to Hutch)
- Spare Wheel
- Lid for Chain Basket
- Spare (Complete Tire & Wheel)
- Side Mount Toolbox with lid
- Upgrade to 12K Axles
- Extra Spring Loaded Jack (Dual Jacks)
- Upgrade to 12", 22 lbs. I-Beam
- 2-Speed Jack System (includes 2nd Jack)
- Upgrade to 14-ply radial tires
- 2-Hydraulic Jacks (includes separate pump & battery)
- Upgrade to 17.5 tires (each tire)
- 2-Hydraulic Jacks (uses SAME PUMP as hydraulic dove tail)
- Weld-on or Sliding Ratchets
- Full Deck over Gooseneck
- Ratchet Rail (per 6' length)
- Extend Metal Track & add 1/2" angle traction cleats (6" OC)
- Blackwood (rubber infused lumber) excellent traction
- Metal Floor (3/16" Diamondplate with crossmembers on 12" centers)



The Dove Tail (DT 1) is a 9-foot HYDRAULIC DOVE TAIL that is fully self-contained, with twin hydraulic cylinders plus pump, battery and remote, all included.

210HGN-27	27 feet
210HGN-29	29 feet
210HGN-32	32 feet
210HGN-34	34 feet
210HGN-36	36 feet

Overall trailer length includes dove tail length