## 5-Ton Narrow Body Dump Trailers

Also Available in Gooseneck

Jelta



**252NBD** 



**252NBD** 

**5-TON NARROW BODY DUMP TRAILERS** 

Also available in Gooseneck

## <u>S P E C I F I C A T I O N S</u>

G.V.W.R	10,400#		
COUPLER	2 5/16" Bulldog Coupler on Leveler Track		
AXLES	Tandem 5,200# Single Wheel		
SUSPENSION	Multi-leaf Slipper Spring with Equalizer		
BRAKES	Electric Brakes on All Axles		
TIRE	ST235/80R16 (10 ply)		
WHEEL	16 x 6, 6-bolt Steel		
FRAME	2" x 5" Tubing		
TONGUE	5" Channel (Double to 10")		
CROSSMEMBERS	3" Channel on 16" Centers		
BED CROSSMEMBERS	3" Channel on 12" Centers		
SAFETY CHAINS	Heavy Duty with Safety Latch Hooks		
JACK	12,000# Spring Loaded Drop Leg Jack		
BED TIE DOWNS	None		
FLOOR	12 Gauge Smooth Steel		
FENDERS	Steel Diamondplate		
DUMP ANGLE	45 Degree Dump Angle (max)		
TARP/MOUNT	Tarp Mount is Standard, Tarp Optional		

HYDRAULIC LIFT HYDRAULIC PUMP CONTROL DUMP BED SIDES REAR GATE/DOOR LOADING RAMPS LIGHTS **ELECTRIC PLUG** PREP PRIMER PAINT PINSTRIPES WIDTH FLOOR HEIGHT STORAGE WIRING REFLECTIVE TAPE SAFETY

Self-Contained Electric/Hydraulic Scissor Lift Front Mount Pump & Battery Inside Toolbox Magnetic Control Unit 24" High, 14 Gauge Smooth Steel Combination Dump/Swing Gate with Cam Latches 6 ft. Loading Ramps Stop, Tail, Turn and Clearance 7-Way RV Style 3-Step Acid Washed with Phosphorus Solution Rust Resistant Epoxy Primer High Solid Urethane **Painted Pinstripes** 84" Wide (approx.) Approx. 29" Front Mounted Toolbox with Lid (in A-Frame) Front Mount in Conduit Required D.O.T. Reflective Taping Emergency Breakaway Switch & Battery Backup

All specifications subject to change without notice.

## <u>MEASUREMENTS</u>

Model	Lgth	Capacity	Α	В
252NBD-10	10'	5.05 cubic yd	120"	76"
252NBD-12	12'	6.07 cubic yd	144"	81"
252NBD-14	14'	7.08 cubic yd	168"	108"

All measurements are approximate.

## <u>O P T I O N S</u>

- Extra Spring Loaded Jack (Dual Jacks)
- Spare Wheel
- 2-Speed Jack System (includes 2nd Jack)
- Spare (Complete Tire & Wheel)
- Shrinkwrap Electrical Connections
- Upgrade to 14-ply Radial Tires
- Convert to Gooseneck Version
- Upgrade to 17.5 Tires (Each Tire)
- Debris Tarp



