

Economy Livestock Trailer

Bumper Pull or Gooseneck

Trailer shown with optional black mod wheels; silver wheels are standard.

Scan for more info on this model!







500 ES ECONOMY LIVESTOCK TRAILER

Bumper Pull or Gooseneck

SPECIFICATIONS

G.V.W.R	7,000 #		
COUPLER (BP)	2" Coupler (2 5/16" Coupler on 18' & up)		
COUPLER (GN)	2 5/16" Gooseneck Coupler		
AXLES	Tandem 3,500#		
SUSPENSION	Dexter Eye-to-Eye Springs		
BRAKES	Electric Brakes on One Axle (check local law for compliance)		
TIRE	15" Radial		
WHEEL	15", 6-bolt		
SPARE	Spare Carrier Included		
FRAME	2 x 3 Angle		
TONGUE	3" Channel		
GOOSENECK	6" Channel		
CROSSMEMBERS	2 x 2 Angle on 16" Centers		
JACK	Top Wind with wheel		
FLOOR	2" Pressure Treated Pine		
SIDES	48" High Embossed, 16 Gauge		
SIDE UPRIGHTS	1 x 2 Tubing on 38" Centers (Approx.)		
SIDE DOOR	Standard Escape Door		
ROOF	18 Gauge Metal with Bows on 24" Centers		
ROOF RADIUS	6" Roof Radius		
NOSE CAP	Standard Aerodynamic Front		

CENTER GATE **REAR DOOR REAR OPENING** FENDERS WINDOW WIRING ELECTRIC PLUG **INTERIOR LIGHTS** EXTERIOR LIGHTS PRE-PREP PREP PRIMER PAINT PINSTRIPES **DECK HEIGHT GRAVEL GUARD** SAFETY SAFETY CHAINS

Standard Gate with Spring-Loaded Slam Latch Standard Full Swing with 1/2 Slider Tail Light Gussets, Pin/Spool Latch for Gate GOOSENECK GATE Standard Gooseneck Gate Steel Teardrop None 14 Gauge in Conduit with Junction Box 7-Way RV Style None D.O.T. Stop, Tail, Turn and Clearance 3-Step Acid Washed with Phosphorus Solution Fenders & Roof Joints Sealed Rust Resistant Epoxy Primer Baked-on High Solid Urethane **Painted Pinstripes** Approx. 14" Deluxe Aluminum Diamondplate REFLECTIVE TAPE Required D.O.T. Reflective Taping Emergency Breakaway Switch & Battery Backup 5/16" Heavy Duty with Safety Latch Hooks

LENGTH WIDTH HEIGHT CENTER GATE

12'	6'	6'6"	Located Just Behind Escape Door
14'	6'	6'6"	Set in Center
16'	6'	6'6"	Set in Center

ΟΡΤΙΟΝS

- 6" Additional Height (per 6")
- Interior Light
- Upgrade to 16" 10-ply radial tires
- Full Rear Drop Ramp (with mat)
- 4-Wheel Electric Brakes
- · Add for full Metal Nose Cap (in lieu of tapered metal front)
- 5' wide
- V-Nose
- Full Spare (Tire & Wheel)
- Add Oval Window in front (BP)





Trailer shown with optional black mod wheels; silver wheels are standard.