

Delta 500 Series



Standard Livestock Trailer

Bumper Pull or Gooseneck

*Scan for more info
on this model!*



Delta

DELTA TRAILERS • 1-800-556-2283 • www.deltatrailers.com



500 SERIES

STANDARD LIVESTOCK TRAILER

S P E C I F I C A T I O N S

G.V.W.R	7,000# & 10,400#	ROOF RADIUS	6" Roof Radius
COUPLER (BP)	2" Coupler (2 5/16" Coupler 18' & Up)	NOSE CAP	Round or Square
COUPLER (GN)	2 5/16" Gooseneck Coupler	CENTER GATE	Standard Gate with Spring-Loaded Slam Latch
AXLES	Tandem 3,500#, Tandem 5,200# on 18' and Up	DECK HEIGHT	Approx. 14"
SUSPENSION	Dexter Eye-to-Eye Springs	REAR DOOR	Standard Full Swing with 1/2 Slider
BRAKES	Electric Brakes on All Axles	REAR OPENING	2" x 4" Tubing Rear Posts with Enclosed Taillights; Pin/Spool Latch for Gate
TIRE	Radial	GOOSENECK GATE	Standard Gooseneck Gate
WHEEL	15" or 16" Depending on Length, 6-bolt	FENDERS	Steel Teardrop
SPARE	Spare Carrier Included	WINDOW	Large Oval (BP), None (GN)
FRAME	3 x 3 Angle (BP) 2 x 3 Angle (GN)	WIRING	14 Gauge in Conduit with Junction Box
TONGUE (BP)	3" Channel	ELECTRIC PLUG	7-Way RV Style
CROSSMEMBERS	2 x 2 Angle on 16" Centers	INTERIOR LIGHTS	None
GOOSENECK	6" Channel	PRE-PREP	3-Step Acid Washed with Phosphorus Solution
EXTERIOR LIGHTS	D.O.T. Stop, Tail, Turn and Clearance	PREP	Polyurethane Joint Sealant
JACK (GN)	12,000# Drop Leg Jack (Spring-Loaded)	PRIMER	Rust Resistant Epoxy Primer
JACK (BP)	Top Wind with Wheel	PAINT	Baked-on High Solid Urethane
FLOOR	2" Pressure Treated Pine	PINSTRIPES	Painted Pinstripes
SIDES	48" High Embossed, 16 Gauge	GRAVEL GUARD	Deluxe Aluminum Diamondplate
SIDE UPRIGHTS	1 x 2 Tubing on 24" Centers	REFLECTIVE TAPE	Required D.O.T. Reflective Taping
SIDE DOOR	Full Escape Door	SAFETY	Emergency Breakaway Switch & Battery Backup
ROOF	18 Gauge Metal with Bows on 24" Centers	SAFETY CHAINS	5/16" Heavy Duty with Safety Latch Hooks

LENGTH	WIDTH	HEIGHT	CENTER GATE	AXLE	TIRE SIZE
10'	6'	6'6"	None	Tandem 3500 # Spring	15" Radial
12'	6'	6'6"	Located Just behind Escape Door	Tandem 3500 # Spring	15" Radial
14'	6'	6'6"	Set in Center	Tandem 3500 # Spring	15" Radial
16'	6'	6'6"	Set in Center	Tandem 3500 # Spring	16" Radial
18'	6'	6'6"	Set at 10' from Rear	Tandem 5200 # Spring	16" Radial
20'	6'	6'6"	Set in Center	Tandem 5200 # Spring	16" Radial

O P T I O N S

- 6'8" Width
- 15" Full Spare (Tire & Wheel)
- 7' OR 7'6" Width (axle upgrade may be required)
- 16" Full Spare (Tire & Wheel)
- 8' Width (axle upgrade may be required)
- Interior Light
- 6" Additional Height
- Woodlined (5/8")
- Smooth Sides (14 gauge)
- Solid Rear Gate (no slider)
- V-Nose
- Full Rear Drop Ramp (with mat)

