# Delta

## 600 DELUXE



**Livestock Trailer** 

**Bumper Pull or Gooseneck** 

Scan for more info on this model!







### ELUXE

#### LIVESTOCK CARRIER

#### SPECIFICATIONS

G.V.W.R 7,000 # & 10,400#

2" Coupler (2 5/16" Coupler on 18' & Up) COUPLER (BP)

2 5/16" Gooseneck Coupler COUPLER (GN)

**AXLES** Tandem 3,500#, Tandem 5,200# on 18' and 20'

**SUSPENSION** Dexter Torflex

**BRAKES** Electric Brakes on All Axles

**TIRE** Radial

WHEEL 15" or 16" Depending on Length, 6-bolt

Spare Carrier Included SPARE **FRAME** 2 x 3 Angle (3 x 3 Angle GN)

**TONGUE (BP)** 3" Channel 6" Channel GOOSENECK

CROSSMEMBERS 2 x 2 Angle on 16" Centers Top Wind with Wheel JACK (BP)

12,000# Drop Leg Jack (Spring-Loaded) JACK (GN)

Pressure Treated Pine FLOOR 2" High Embossed, 16 Gauge **SIDES 48"** 1 x 2 Tubing on 24" Centers SIDE UPRIGHTS SIDE DOOR (BP) Standard Escape Door Full Escape Door SIDE DOOR (GN)

**ROOF** 18 gauge Metal with Bows on 24" Centers

**ROOF RADIUS** 6" Roof Radius **NOSE CAP** Round, Square (Other Styles Optional)

**CENTER GATE** Standard Gate with Spring-Loaded Slam Latch

Full Swing with 1/2 Slider on Rollers **REAR DOOR** 

**REAR OPENING** 3x5 Tubing Uprights with Slam Latch for Gate

**GOOSENECK GATE** Standard Gooseneck Gate

**FENDERS** Steel Teardrop Large Oval in Front WINDOW (BP)

WINDOW (GN) None

14 Gauge in Conduit with Junction Box WIRING

**ELECTRIC PLUG** 7-Way RV Style **INTERIOR LIGHTS** Standard Dome Lights

All D.O.T. Required Lighting Plus Quad Tail Lights **EXTERIOR LIGHTS** PRE-PREP 3-Step Acid Washed with Phosphorus Solution

**PREP** All Joints Sealed with Polyurethane Rust Resistant Epoxy Primer **PRIMER PAINT** Baked-on High Solid Urethane

**PINSTRIPES** Painted Pinstripes Approx. 14" **DECK HEIGHT** 

**GRAVEL GUARD** 

Aluminum Diamondplate **REFLECTIVE TAPE** Required D.O.T. Reflective Taping

Emergency Breakaway Switch & Battery Backup **SAFETY** 5/16" Heavy Duty with Safety Latch Hooks **SAFETY CHAINS** 

<u>Length</u>	<u>Width</u>	<u>Height</u>	Center Gate	<u>Axle</u>	<u>Tires</u>
10'	6'	6'6"	None	Tandem 3500 # Torsion	15" Radial
12'	6'	6'6"	Located Just Behind Escape Door	Tandem 3500 # Torsion	15" Radial
14'	6'	6'6"	Set in Center	Tandem 3500 # Torsion	15" Radial
16'	6'	6'6"	Set in Center	Tandem 3500 # Torsion	16" Radial
18'	6'	6'6"	Set at 10' from Rear	Tandem 5200 # Torsion	16" Radial
20'	6'	6'6"	Set in Center	Tandem 5200 # Torsion	16" Radial

#### OPTIONS

- 6'8" Width
- 15" or 16" Full Spare (Tire & Wheel)
- 7', 7'6" or 8' Width (axle upgrade may be required)
- Extra Interior Light
- 6" Additional Height
- Woodlined (5/8")
- Smooth Sides (14 gauge)
- · Solid Rear Gate (no slider)
- Full Rear Drop Ramp (with mat)
- V-Nose Front



