





UTILITY TRAILERS DELTA 135UT AND 235UT

SPECIFICATIONS

G.V.W.R. 3,500#, 70,000# COUPLER 2" Coupler

AXLES Single & Tandem 3,500# Dexter Multi-leaf Slipper Spring with Equalizer **SUSPENSION**

TIRE ST225/75R15 (10 ply)

WHEEL 15 x 6, 6-bolt **FRAME** 2 x 3 Angle Iron

A-FRAME 3" Channel on single, 4" Channel on Tandems

CROSSMEMBERS 2 x 2 Angle Iron on 24" Centers

SAFETY CHAINS 3/8' Heavy Duty with Safety Latch Hooks

2000# Top Wind Jack with Wheel **JACK** 2 x 2 Tubing Top Rail SIDE RAILS

UPRIGHTS 2 x 2 Angle (Single Axles), 1 x 2 Tubing (Tandems)

Tie Down Rings **TIE RINGS**

ELECTRIC PLUG 7-Way RV Style

PREP 3-Step Acid Washed with Phosphorus Solution

Rust Resistant Epoxy Primer **PRIMER**

High Solid Urethane **PAINT PINSTRIPES** Painted Pinstripes

60" & 76" Widths (Custom Sizes Available) OVERALL WIDTH

DECK HEIGHT Approx. 19" Standard

Electric Brakes On One Axle (Tandems Only) **BRAKES DOVE TAIL** 24" Dove Tail Available As an Added Option 48" High, Full Width Spring Assisted Ramp **RAMP**

Front A-Frame Toolbox Optional **TOOLBOX**

WIRING Mounted in Conduit

REFLECTIVE TAPE Required D.O.T. Reflective Taping

SAFETY Emergency Breakaway Switch & Battery Backup 2" Pressure Treated Pine **FLOOR**

LIGHTS All LED Stop, Tail, Turn and Clearance All specifications subject to change without notice.

<u>Model</u>	Length (ft.)	Width (in.)	<u>Axles</u>
135UT-510	10'	60"	Single, 3500#, No brake
135UT-612	12'	76"	Single, 3500#, No brake
135UT-614	14'	76"	Single, 3500#, No brake
235UT-612	12'	76"	Tandem, 3500#, Brakes on one axle
235UT-614	14'	76"	Tandem, 3500#, Brakes on one axle
235UT-616	16'	76"	Tandem, 3500#, Brakes on one axle

Photos show OPTIONAL equipment. All measurements are approximate



OPTIONS

- 24" Dove Tail with 30" High Rear Ramp
- Front Mounted Modern Toolbox with Locking Lid
- Full Running Boards
- Metal Floor (3/16" Diamondplate with crossmembers on 12" centers)
- Spare (Complete Tire & Wheel)
- Black Standard Wheels
- Custom Wheels
- Custom Paint Color
- · Add brakes to any axle (if not equipped)

